

Celfrost

A Middleby Company, USA

Adding Freshness into your recipes!



Refrigerated Reach in Cabinets

Celfrost Professional Reach In Cabinets suitable for 2 x GN 1/1 sizes are built in SS304 with reliable Danfoss / Embraco or equivalent compressors, LED temperature display, rounded internal edges for complete hygiene, removable magnetic gaskets for ease of cleaning, self closing doors with heaters to prevent condensation and heavy duty lockable castors. Available in Chillers or Deep Freezers with two or four door options.

Features:

- Rounded internal edges
- Removable magnetic gaskets
- Self closing doors
- Auto defrost
- Eco friendly refrigerant
- Food grade steel
- Uniform cooling
- Adjustable trays



GN 650 TNM (New)/
GN 650 BTM (New)



GN 1410 TNM (New)/
GN 1410 BTM (New)



GN 2100 TN
GN 2100 BT



GN 3100 TN
GN 3100 BT

Undercounters

While retaining the basic features of the Reach in Cabinets mentioned above, these refrigerated work tables, mounted on heavy duty lockable castors, pull out condensing unit, combine storage and preparation thereby enhancing the effectiveness of kitchen professionals and are suitable for GN 1/1 sizes. Chillers or Deep Freezers available in 2 and 3 door options.

Prep Counters

Celfrost Professional Prep Counters desserts and more. Mounted on castors and available in 2 and 3 doors, frost free & static with fan assist cooling variants.



SH 2080
SH 2100/800[#]



PSE 201*
(Also available in 3 doors
model PSE 301*)



SH 3080
SH 3100/800[#]

*Static Cooling & Manual Defrost.

[#]SH 2100/800 & SH 3100/800 are in SS 201

Saladettes & Countertop Displays

The Saladettes come with a refrigerated GN compatible top (Pans not included) that can take in frozen yogurt toppings, salads etc. It also has a night cover. 2 & 3 Door Refrigerated section underneath is handy to store additional foodstuff. The Countertop display comes with a glass sneeze guard; is equipped with its own refrigeration unit and accepts GN ¼ pans (not included).




SE 900

SE 903



VRX 1200/330, VRX 1400/330

S 900/SE 900



SE 903



Frost Top & Cooling Well



3F

GN 3V

Blast Chillers & Shock Freezers

The powerful Celfrost Professional Blast Chillers / Freezers are most ideal for reducing the temperature of cooked food from 80°C to 3°C or -18°C rapidly, thereby rendering it safe from bacterial growth and fit for ensuing storage and consumption later on. Available in 4 capacities, they are suitable for both GN 1/1 and 400x 600 mm tray sizes.



D3/D5

D10/D14

Gastronorm (GN) Dimensions : L x W

GN 1/1	>	530 mm x 327 mm
GN 1/2	>	327 mm x 265 mm
GN 1/3	>	327 mm x 176 mm
GN 2/3	>	354 mm x 325 mm
GN 1/4	>	265 mm x 163 mm
GN 1/6	>	176 mm x 163 mm

Depth in case of pans can vary from 65, 100 or 150 mm
*GN Pan/Tray is not part of unit.

E-Series - Ventilated Reach Ins & Undercounters

Bigger space inside due to Insulated Evaporator at top in Reachins with all essential features like Removable gaskets, heavy duty castors, GN compatible, Danfoss / Embraco Compressor, Slide out Condenser unit (in undercounters), Digital controller, lock and many more to make it user friendly and hassle-free operation.



GN 2200 TNE/GN 2200 BTE/VUC 2101 TN*
(Also available in 3 door models GN 3200 TNE/GN 3200 BTE/VUC 3101 TN*)



GN 700 TNME / GN 700 BTME /
VRI 550 TNM*



GN 1500 TNME / GN 1500 BTME
/ VRI 1100 TNM*

Note: All units are without pans.

E-Series is with SS 201/SS 430

*VUC / VRI Series are not GN Compatible

Technical Specifications

Product	Model	Dimension (WxDxH) mm	Volume (in ltrs.)	Design (GN Compatibility)	No. of Doors	No. of shelves	Temperature Range (°C)	Input Power (in watts)	Refrigerant
Reach-in Refrigerators (Ventilated Cooling)	GN 650 TNM (New)	680 x 800 x 2010	600	2 x GN 1/1	2	3	2 to 8°C*	375	R134a
	GN 1410 TNM (New)	1340 x 800 x 2010	1200	2 x GN 1/1	4	6	2 to 8°C*	800	R134a
	GN 700 TNME	740 x 830 x 2010	650	2 x GN 1/1	2	3	2 to 8°C*	400	R290
	GN 1500 TNME	1480 x 830 x 2010	1300	2 x GN 1/1	4	6	2 to 8°C*	670	R290
	VRI 550/555 TNM	680 x 710 x 2010	550	-	2	3	2 to 8°C#	210	R290
	VRI 1100/1111 TNM	1340 x 710 x 2010	1100	-	4	6	2 to 8°C#	400	R290
Reach-in Freezers (Ventilated Cooling)	GN 650 BTM (New)	680 x 800 x 2010	600	2 x GN 1/1	2	3	-18 to -22°C*	800	R404a
	GN 1410 BTM (New)	1340 x 800 x 2010	1200	2 x GN 1/1	4	6	-18 to -22°C*	1060	R404a
	GN 700 BTME	740 x 830 x 2010	650	2 x GN 1/1	2	3	-18 to -22°C#	800	R290
	GN 1500 BTME	1480 x 830 x 2010	1300	2 x GN 1/1	4	6	-18 to -22°C#	1060	R290
	VRI 555 BTM	680 x 710 x 2010	550	-	2	3	-18 to -22°C#	800	R290
	VRI 1111 BTM	1340 x 710 x 2010	1100	-	4	6	-18 to -22°C#	1060	R290
Undercounter Chillers (Ventilated Cooling)	GN 2100 TN	1360 x 700 x 860	282	1 x GN 1/1	2	2	2 to 8°C*	375	R134a
	GN 3100 TN	1795 x 700 x 860	417	1 x GN 1/1	3	3	2 to 8°C*	375	R134a
	GN 2200 TNE	1360 x 700 x 850	282	1 x GN 1/1	2	2	2 to 8°C*	375	R600a
	GN 3200 TNE	1795 x 700 x 850	417	1 x GN 1/1	3	3	2 to 8°C*	375	R600a
	VUC 2101/2111 TN	1360 x 600 x 850	228	-	2	2	2 to 8°C#	215	R290
	VUC 3101/3111 TN	1795 x 600 x 850	339	-	3	3	2 to 8°C#	230	R290
	TUC750C	705 x 760 x 902	190	-	1	1	0 to 5°C*	375	R290
Undercounter Freezers (Ventilated Cooling)	GN 2100 BTM	1360 x 700 x 860	282	1 x GN 1/1	2	2	-10 to -20°C*	800	R404a
	GN 3100 BTM	1795 x 700 x 860	417	1 x GN 1/1	3	3	-10 to -20°C*	880	R404a
	GN 2200 BTE	1360 x 700 x 850	282	1 x GN 1/1	2	2	-10 to -20°C#	875	R600a
	GN 3200 BTE	1795 x 700 x 850	417	1 x GN 1/1	3	3	-10 to -20°C#	890	R600a
	VUC 2111 BT	1360 x 600 x 850	228	-	2	2	-10 to -20°C#		R290
	VUC 3111 BT	1795 x 600 x 850	339	-	3	3	-10 to -20°C#		R290
	TUC750F	705 x 760 x 902	190	-	1	1	-18 to -22°C*	375	R290
Prep Counters (Ventilated Cooling)	SH 2080	1510 x 800 x 1050	337	8 x GN 1/3	2	2	2 to 8°C#	335	R134a
	SH 2100/800	1510 x 800 x 1085	337	8 x GN 1/3	2	2	2 to 8°C**	375	R290
	SH 3080	2020 x 800 x 1050	497	10 x GN 1/3	3	3	2 to 8°C#	495	R134a
	SH 3100/800	2020 x 800 x 1050	497	10 x GN 1/3	3	3	2 to 8°C**	400	R290
Prep Counters (Static Cooling with Fan Assist)	PSE 201	900 x 700 x 970	240	8 x GN 1/6	3	3	2 to 8°C**	350	R290
	PSS 222-2	900 x 700 x 970	240	8 x GN 1/6	3	3	2 to 8°C*	350	R290
	PSE 301	1365 x 700 x 970	360	12 x GN 1/6	3	3	2 to 8°C**	375	R290
	PSS 322-3	1365 x 700 x 970	360	8 x GN 1/6	3	3	2 to 8°C*	375	R290
Counter Top Displays (Static Cooling)	VRX 1200/330	1200 x 335 x 225	-	5 x GN 1/4	-	-	2 to 8°C**	209	R134a
	VRX 1400/330	1400 x 335 x 435	-	6 x GN 1/4	-	-	2 to 8°C**	209	R134a
Saladettee (Static Cooling with Fan Assist)	SE 900	900 x 700 x 850	-	2 x GN 1/1 + 2 x GN 1/4	2	2	2 to 8°C**	350	R290
	SE 903	1365 x 700 x 850	-	4 x GN 1/1	3	3	2 to 8°C**	375	R290
Frost Top	3F	1119 x 695 x 432	NA	NA	NA	NA	-10°C**	500	R134a
Ventilated Cooling Well	GN 3V (GN-3L)	1122 x 688 x 636	NA	3 x GN 1/1	NA	NA	2 to 8°C**	280	R134a

Product	Model	Exterior Dimension (WxDxH) mm	Internal Dimension (WxDxH) mm	Pan Support (GN 1/1)	Pan Support (400 x 600 mm)	Net Weight (in kgs)	Power Supply	Refrigerant	Temperature Drop (°C)	Input Power (in watts)	Mode of Refrigeration
Blast Chillers/Freezers	D3	800 x 815 x 945	660 x 640 x 330	3 Sets	3 Sets	80	230V/50Hz	R404a	90°C to 3°C in 90 minutes & 90°C to -18°C in 240 minutes	703	Ventilated
	D5	800 x 815 x 1015	660 x 640 x 400	5 Sets	5 Sets	95	230V/50Hz	R404a		801	Ventilated
	D10	800 x 815 x 1645	660 x 640 x 870	10 Sets	10 Sets	150	230V/50Hz	R404a		1298	Ventilated
	D14	800 x 815 x 2117	660 x 640 x 1170	14 Sets	14 Sets	210	380V/50Hz/3Ph	R404a		2000	Ventilated

* Tested to perform under ambient temperature of 42°C

** Tested to perform under ambient temperature of 32°C

Tested to perform under ambient temperature of 38°C

With a view to ensure ongoing product enhancement/development, Middleby Celfrost reserves the right to change any specification, without prior notice.

ISO9001:2000 CE CCC U RoHS

Note: 1. Images are for representation, actual product might vary. 2. Specifications might change due to continuous product development. 3. Accessories are optional.



Middleby Celfrost Innovations (P) Ltd.

Corp. Office : Unit Nos. SF-713 — 716, 7th Floor, JMD Megapolis, Sohna Road, Sector 48, Gurugram - 122 018, Haryana, India.

Tel. : +91 124 482 8500, Fax : +91 124 427 9663, E-mail : corp@middlebycelfrost.com, Web : www.middlebycelfrost.com

Toll Free Customer Service No.: 1800-102-1980 • service.india@middlebycelfrost.com

For sales related queries :-

Call: +91 124 4828500 • Email: sales@middlebycelfrost.com